



PERRY JOHNSON LABORATORY ACCREDITATION, INC.

Certificate of Accreditation

Perry Johnson Laboratory Accreditation, Inc., has assessed the Laboratory of:

***CDM Testing Laboratory
1124 North Second Street
Baldwyn, MS 38824***

(Hereinafter called the Organization) and hereby declares that Organization is accredited in accordance with the recognized International Standard:

ISO/IEC 17025: 2005

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (as outlined by the joint ISO-ILAC-IAF Communiqué dated January 2009):

***Physical Testing of Foam and Foam Laminates for the
Automotive, Bedding, and Other Industries
(As detailed in the supplement)***

Such testing and/or calibration services shall only be offered at or from the address given above. This Accreditation is granted subject to the system rules governing the Accreditation referred to above, and the Organization hereby covenants with the Accreditation body's duty to observe and comply with the said rules.

For PJLA:

The validity of this certificate is mandated through ongoing surveillance.

Tracy Szerszen
President/Operations Manager
Perry Johnson Laboratory
Accreditation, Inc. (PJLA)
26555 Evergreen, Suite 1325
Southfield, Michigan 48076

<i>Initial Accreditation Date:</i> May 30, 2007	<i>Issue Date:</i> May 06, 2009	<i>Revision Date:</i> November 20, 2009	<i>Expiration Date:</i> May 05, 2011
<i>Accreditation No.:</i> 59424	<i>Certificate No.:</i> L09-48-R1	<i>Page No.:</i> Page 1 of 3	



Certificate of Accreditation: Supplement

CDM Testing Laboratory
 1124 North Second Street
 Baldwin, MS 38824

Accreditation is granted to this facility to perform the following testing:

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OF PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED
Mechanical Testing	Foam and Foam Laminates	Staining	ASTM D925 (Method A)
		Density	ASTM D3574 (Test A)
		Indentation Force Deflection	ASTM D3574 (Test B1)
		Compression Force Deflection	ASTM D3574 (Test C)
		Constant Deflection Compression Set	ASTM D3574 (Test D)
		Tension Test (Tensile + Elongation)	ASTM D3574 (Test E)
		Tension Test (Tear)	ASTM D3574 (Test F)
		Air Flow	ASTM D3574 (Test G)
		Resilience Test (Ball Rebound)	ASTM D3574 (Test H)
		Dynamic Fatigue Constant Force Pounding	ASTM D3574 (Test I ₃)
		Steam Autoclave Aging	ASTM D3574 (Test J)
		Dry Heat Aging	ASTM D3574 (Test K)
		Cleanability	GM 6291M (Section 3.1.2)
		Flammability	GM 9070P
		Mildew Resistance	GM 9128P
		Resistance to Odor	GM 9130P (Section 3.1)
		Wicking	GM 9146P (Method A, para 4.1)
		Accelerated Aging and Steaming	GM 9200P
		Crease Resistance	GM 9201P
		Resistance to Odor	SAE J1351
		Characteristics of Fogging	SAE 1756, Photometric
Flammability	UL 94 (HBF, HF-1, HF-2) ASTM D 4986-03		
Flammability	FMVSS 302		
		Flammability	CAL T.B. 117 (Section A, Part I)



Certificate of Accreditation: Supplement

CDM Testing Laboratory
1124 North Second Street
Baldwyn, MS 38824

Accreditation is granted to this facility to perform the following testing:

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OF PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED
Mechanical Testing	Foam and Foam Laminates	Smoldering Test	CAL T.B. 117 (Section D, Part II)
		UFAC	Filling/Padding Component Test Method – 1990 Part A
		Ash Content	ASTM D2617-W
		Heat Sag	REL-01
		Tear Resistance	REL-02
		Water Absorption	REL-03
		Tension	REL-04
		Compression Force	REL-05
		Cell Count	REL-06
		Air Flow	REL-07-B
Visco Recovery	REL-08 ASTM D3574 (Test M)		