

# PERRY JOHNSON LABORATORY ACCREDITATION, INC.

## *Certificate of Accreditation*

*Perry Johnson Laboratory Accreditation, Inc., has assessed the Laboratory of:*

**Complete Inspection Specialists, Inc  
6621 Cotter Avenue  
Sterling Heights, MI 48314**

*(Hereinafter called the Organization) and hereby declares that Organization is accredited in accordance with the recognized International Standard:*

**ISO/IEC 17025: 2005**

*This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (as outlined by the joint ISO/IEC/JAF Communiqué dated January 2009):*

**CMM Dimensional Measurement and Inspection of Models, Tooling, Fixtures and Parts  
(As detailed in the supplement)**

*Such testing and/or calibration services shall only be offered at or from the address given above. This Accreditation is granted subject to the system rules governing the Accreditation referred to above, and the Organization hereby covenants with the Accreditation body's duty to observe and comply with the said rules.*

For PJLA:

*The validity of this certificate is mandated through ongoing surveillance.*

---

Tracy Szerszen  
President/Operations Manager  
Perry Johnson Laboratory  
Accreditation, Inc. (PJLA)  
26555 Evergreen, Suite 1325  
Southfield, Michigan 48076

*Initial Accreditation Date:*  
July 23, 2003

*Accreditation No.:*  
59086

*Issue Date:*  
August 02, 2009

*Certificate No.:*  
L09-79

*Expiration Date:*  
August 01, 2011

*Page No.:*  
Page 1 of 2

# Certificate of Accreditation: Supplement

**Complete Inspection Specialists, Inc**  
6621 Cotter Avenue  
Sterling Heights, MI 48314

*Accreditation is granted to this facility to perform the following testing:*

<b>FIELD OF TEST</b>	<b>ITEMS, MATERIALS OR PRODUCTS TESTED</b>	<b>SPECIFIC TESTS OR PROPERTIES MEASURED</b>	<b>SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED</b>	<b>RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT</b>
Dimensional Measurement	Fixtures, Parts, Models, and Molds	CMM #1 TPINCL2665124407	X= 304.8 cm (120 in) Y= 152.4 cm (60 in) Z= 160.02 cm (63 in)	0.02 mm
		CMM #2 TPINCL756090126	X= 304.8 cm (120 in) Y= 152.4 cm (60 in) Z= 160.02 cm (63 in)	0.01 mm