

PERRY JOHNSON LABORATORY ACCREDITATION, INC.

Certificate of Accreditation

Perry Johnson Laboratory Accreditation, Inc. has assessed the Laboratory of:

Colorado Metallurgical Services

10605 East 25th Avenue, Aurora, CO 80010

(Hereinafter called the Organization) and hereby declares that Organization is accredited in accordance with the recognized International Standard:

ISO/IEC 17025:2017

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (as outlined by the joint ISO-ILAC-IAF Communiqué dated April 2017):

Chemical Testing, Mechanical, Metallographic Examination of Metal Alloys, Weld Qualification and Failure Analysis, and Non-Destructive (UT, MT, & PT) (As detailed in the supplement)

Accreditation claims for such testing and/or calibration services shall only be made from addresses referenced within this certificate. This Accreditation is granted subject to the system rules governing the Accreditation referred to above, and the Organization hereby covenants with the Accreditation body's duty to observe and comply with the said rules.

For PJLA:

Jeacy Szuszen

Tracy Szerszen President

Perry Johnson Laboratory Accreditation, Inc. (PJLA) 755 W. Big Beaver, Suite 1325 Troy, Michigan 48084

 Initial Accreditation Date:
 Issue Date:
 Expiration Date:

 September 03, 2013
 November 22, 2023
 December 31, 2026

 Accreditation No.:
 Certificate No.:

 72916
 L23-850

The validity of this certificate is maintained through ongoing assessments based on a continuous accreditation cycle. The validity of this certificate should be confirmed through the PJLA website: <u>www.pjlabs.com</u>

Page 1 of 9



Colorado Metallurgical Services 10605 East 25th Avenue, Aurora, CO 80010

10605 East 25th Avenue, Aurora, CO 80010 Contact Name: Josh Belt Phone: 563-200-3240

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED	RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT
Chemical ^F	Aluminum and	Optical Emission	ASTM E1251	Beryllium: 0.005 %
	Aluminum Alloys	Spectrometry (OES)		Chromium: 0.001 %
				Copper: 0.002 %
				Iron: 0.001 %
				Lead: 0.001 %
				Magnesium: 0.001 5 %
				Manganese: 0.003 %
				Nickel: 0.001 %
				Silicon: 0.001 %
				Tin: 0.004 %
				Titanium: 0.003 %
				Vanadium: 0.003 %
				Zinc: 0.005 %
				Zirconium: 0.004 %
				Aluminum: Remainder
	Cast Iron		ASTM E1999	Aluminum: 0.003 %
				Boron: 0.000 1 %
				Carbon: 0.002 %
				Chromium: 0.003 %
				Cobalt: 0.004 %
				Copper: 0.001 %
				Lead: 0.002 %
				Magnesium: 0.005 %
				Manganese: 0.001 5 %
				Molybdenum: 0.001 %
				Nickel: 0.01 %
				Phosphorus: 0.003 %
				Silicon: 0.002 %
				Sulfur: 0.001 %
				Titanium: 0.003 %
				Tin: 0.005 %
				Tungsten: 0.003 %
				Vanadium: 0.001 %
				Iron: Remainder



Colorado Metallurgical Services 10605 East 25th Avenue, Aurora, CO 80010

10605 East 25th Avenue, Aurora, CO 80010 Contact Name: Josh Belt Phone: 563-200-3240

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED	RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT
Chemical ^F	Copper and	Optical Emission	Laboratory	Aluminum: 0.001 %
	Copper Alloys	Spectrometry (OES)	In house Method	Beryllium: 0.001 %
				Carbon: 0.001 %
				Cobalt: 0.001 %
				Iron: 0.001 %
				Lead: 0.003 %
				Manganese: 0.003 %
				Nickel: 0.002 %
				Phosphorus: 0.001 %
				Silicon: 0.001 %
				Sulfur: 0.000 8 %
				Tin: 0.002 %
				Zinc: 0.001 %
				Copper: Remainder
	Carbon Steel and		ASTM A751	Aluminum: 0.003 %
	Low Alloy Steel		ASTM E415	Boron: 0.000 1 %
				Carbon: 0.002 %
			X A	Chromium: 0.003 %
				Cobalt: 0.004 %
				Columbium: 0.005 %
				Copper: 0.001 %
				Lead: 0.003 %
				Manganese: 0.001 5 %
				Molybdenum: 0.001 %
				Nickel: 0.01 %
				Phosphorus: 0.003 %
				Selenium: 0.001 %
				Silicon: 0.002 %
				Sulfur: 0.001 %
				Tin: 0.002 %
				Titanium: 0.003 %
				Tungsten: 0.005 %
				Vanadium: 0.001 %
				Zirconium: 0.004 %
				Iron: Remainder



Colorado Metallurgical Services 10605 East 25th Avenue, Aurora, CO 80010

10605 East 25th Avenue, Aurora, CO 80010 Contact Name: Josh Belt Phone: 563-200-3240

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED	RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT
Chemical ^F	Metal	Combustion –	ASTM E1019	Carbon: 0.001 % to 4.5 %
		LECO		Nitrogen: 0.000 5 % to 0.5 %
				Oxygen: 0.000 5 % to 0.1 %
				Sulfur: 0.002 % to 0.6 %
	Nickel and Nickel	Optical Emission	ASTM E3047	Aluminum: 0.029 %
	Alloys	Spectrometry (OES)	Laboratory	Boron: 0.000 2 %
			In nouse Method	Carbon: 0.002 %
				Chromium: 0.001 %
				Cobalt: 0.014 %
				Columbium: 0.001 %
				Copper: 0.004 %
				Iron: 0.076 %
				Manganese: 0.018 %
				Molybdenum: 0.001 %
				Phosphorus: 0.001 %
				Silicon: 0.000 6 %
				Sulfur: 0.001 %
				Titanium: 0.005 %
				Tungsten: 0.001 %
				Vanadium: 0.001 %
				Zirconium: 0.001%
				Nickel: Remainder
Chemical FO	Quantitative Analysis	Element Range is	ASTM E1621	Depending Upon the Element
	of Metallic Products or Metal Alloys	Magnesium to		Analyzed in this Element Range $DI : 0.01\%$ to 0.1%
Chemical ^F	Stainless Steel	Optical Emission	ASTM A751	Aluminum: 0.003 %
		Spectrometry (OES)	ASTM E1086	Boron: 0.000 1 %
				Carbon: 0.002 %
				Chromium: 0.003 %
				Cobalt: 0.004 %
				Columbium: 0.005 %
				Copper: 0.001 %
				Manganese: 0.001 5 %
				Molybdenum: 0.001 %
				Nickel: 0.01 %
				Phosphorus: 0.003 %
				Selenium: 0.001 %
Issue: 11/20	D23 This su	pplement is in conjunct	ion with certificate #L23	-850 Page 4 of 9



Colorado Metallurgical Services 10605 East 25th Avenue, Aurora, CO 80010

10605 East 25th Avenue, Aurora, CO 80010 Contact Name: Josh Belt Phone: 563-200-3240

Accreditation is granted to the facility to perform the following testing

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED	RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT
Chemical ^F	Stainless Steel	Optical Emission	ASTM A751	Silicon: 0.002 %
		Spectrometry (OES)	ASTM E1086	Sulfur: 0.001 %
				Tin: 0.002 %
				Titanium: 0.003 %
				Tungsten: 0.005 %
				Vanadium: 0.001 %
				Zirconium: 0.004 %
				Iron: Remainder
	Titanium		ASTM E2626	Aluminum: 0.002 %
				Carbon: 0.001 %
				Iron: 0.001 5 %
				Manganese: 0.001 5 %
				Molybdenum: 0.003 %
				Nickel: 0.005 %
				Silicon: 0.001 %
				Tin: 0.001 %
				Vanadium: 0.003 %
				Zirconium: 0.001 %
				Titanium: Remainder
	Tool Steel		ASTM A751	Aluminum: 0.001 %
			ASTM E1086	Carbon: 0.002 %
				Chromium: 0.01 %
				Cobalt: 0.007 %
				Copper: 0.001 %
				Magnesium: 0.005 %
				Manganese: 0.001 5 %
				Molybdenum: 0.001 %
				Nickel: 0.01 %
				Phosphorus: 0.003 %
				Silicon: 0.01 %
				Sulfur: 0.001 %
				Tin: 0.005 %
				Titanium: 0.002 %
				Tungsten: 0.01 %
				Vanadium: 0.05 %
				Iron: Remainder

This supplement is in conjunction with certificate #L23-850



Colorado Metallurgical Services 10605 East 25th Avenue, Aurora, CO 80010

10605 East 25th Avenue, Aurora, CO 80010 Contact Name: Josh Belt Phone: 563-200-3240

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED	RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT
Mechanical F	All Metals	Brinell Hardness	ASTM E10	500 kgf
			SAE J417	3 000 kgf
		Charpy, V-notch Impact	ASTM E23	Up to 139.5 J
		Testing	ASTM A370	(Up to 102.9 lbf•ft)
		Microhardness- Knoop	ASTM E384	10 g, 25 g, 50 g, 100 g,
			ASTM B578	200 g, 300 g, 500 g
		Microhardness- Vickers	ASTM E384	5 kg 10 kg
		Rockwell Hardness	ASTM E18	Scale: A, B, C, D, E, F
		Rockwell Hardness -	ASTM E18	Scale: 15 N, 30 N, 45 N 15 T,
		Superficial		30 T, 45 T
		Room Temperature -	ASTM E8	4 N to 711 680 N
		Tensile & Bolt Test	ASTM A370	(1 lbf to 160 000 lbf)
			ASTM B557	
			ASTM F606	
			SAE J416	
			SAE J429	
			SAE J1216	
		Wet Tape Adhesion	MIL-DTL-5541	Qualitative Visual
		Testing	ASIM D3339	
			6301.3	\supset
	Cast Stainless Steel, Duplex Stainless Steels	Ferrite Content Testing	ASTM A799	0.5 % to 83.2 %
	Metal	Bend Testing	ASTM E190	1.27 mm to 304.8 mm
			ASTM E290	(0.05 in to 12 in)
			ASTM A370	OD Ram
		Hydrogen Embrittlement	ASTM F519	200 Hr
		Relief		Up to 44 482 N (10 000 lbf)
		Jominy Testing	ASTM A255	Oven to 1 288 °C
		Post Weld Stress Relief	AWS D1.1 ASME Section VIII	(2 350 °F)
		Proof Load	ASTM A370	4 N to 711 680 N
			ASTM F606	(1 lbf to 160 000 lbf)
			SAE J429	
			SAE J995	
			SAE J1216	
		Wedge Tension	ASTM A370	
			ASTM F606	
			SAE J429	
			SAE J1216	



Colorado Metallurgical Services 10605 East 25th Avenue, Aurora, CO 80010

Contact Name: Josh Belt Phone: 563-200-3240

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED	RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT
Mechanical ^F	Steels and Cast Steel, Cold Worked Steel, Stainless and High Temp Resistant Steel, Gray and Ductile Cast Iron, Aluminum Alloys Cast and Wrought, Copper and Copper Alloys	Leeb Hardness Testing	ASTM A956	All Leeb Values are Automatically Converted per ASTM E140 to One of the Following Scales: 19-70 HMMRC; 19-70 HRC; 67-638 HB; 35-950 HV; 60-86 HRA; 29-107 HRB; 69-74 HR15N; 88-96 HR15T; 100-107 HRH (AL Only); 75- 106 HRE (AL Only)
Mechanical –	Aluminum,	Chemical Passivation	ASTM A967	Qualitative Visual
Corrosion ^F	Stainless &	Screening/Salt Spray	ASTM B117	Weight Loss (g)
	Nickel Alloys	(Fog)/Copper Sulfate		0.001 g to 560 g
		Screening Comparing Day 1 Test		0.000 01 g to 159 g
		Corrosion – Bend Test	ASTM A262 Practice E	Qualitative visual
		Corrosion -	ASTM A262	
		Microstructure Exam	Practice A	
	· · · · · · · · · · · · · · · · · · ·	Corrosion -	ASTM B117	
		Visual	ASTM G38	
			ASTM G49	
			ASTM G34	
			ASTM GI10	
		Pitting & Crevice	ASTM G28	Weight Loss (g)
		Latergropular Corregion	ASIM G48	0.001 g to 560 g
		Susceptibility	ASTM G1	0.000 01 g to 159 g
		Buseephonny	ASTM A262	
			Practice B. C. F	
Mechanical –	Metal	Failure Analysis	ASM Handbook.	Qualitative Visual
Failure Analysis		Investigation	Volume 11, Standard	
FO			Industry Practices	
		Fractographic	ASM Handbook,	
		Investigation	Volume 12, Standard	
			Industry Practices	



Colorado Metallurgical Services 10605 East 25th Avenue, Aurora, CO 80010

10605 East 25th Avenue, Aurora, CO 80010 Contact Name: Josh Belt Phone: 563-200-3240

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED	RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT
Mechanical –	Metal	Coating Thickness	ASTM B487	0.002 5 mm
Metallurgy ^F				(0.000 1 in)
				Minimum Optical
		Coating Weight	ASTM A90	0.001 g to 560 g
			ASTM A428	
			MIL-A-8625	
		Grain Flow	11-C-490F	Qualitative Vigual
			ASTM E340	Qualitative visual
		Grain Size	ASIM EI12	
		Inclusions	ASTM E45	
		Macroetch Evaluation	ASTM E381	
			MIL-STD-867C	
		Macroetching	ASTM E340	
			ASTM E407	
	Tool Steel	Case Depth	SAE J423	0.076 mm
			ASTM E384	(0.003 m)
			ASTM E407	
		and End Grain Ditting	ASTM F2111	$(0.000 \ 2 \ \text{m}) \text{ at } 500 \ \text{A}$
		Matallagraphia	ASM Handbook	D.L 0.003 1 IIIII
		Evaluation	Volume 0	$20 \times t_0 1 000 \times 1000 \times 1000 \times 1000 \times 1000 \times 1000 \times 1000 \times 10000 \times 100000000$
		Evaluation	Metals Handbook	20 X 10 1 000 X
			8th Ed Volume 7	SEM: 10 X to 10 000 X
			Standard Industry	
			Practices	
		L L	ASTM A247	
			ASTM E883	
		Metallographic Sample	ASTM E3	Up to 1 µm Alumina
		Preparation	ASTM E340	
			ASTM E1920	
			ASM Handbook	
			Volume 9	
		Presence of	ASTM E1077	D.L.= 0.013 mm (0.000 5 in)
		Carburization /	ASTM E384	Minimum
		Decarburization	ASTM E407	
			ASIM F2328	
			SAE J121 SAE J419	



Colorado Metallurgical Services

10605 East 25th Avenue, Aurora, CO 80010 Contact Name: Josh Belt Phone: 563-200-3240

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED	RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT
Mechanical –	All Solid	Microscopic Evaluation	ASTM B748	10 X to 10 000 X
SEM ^F	Materials		ASTM E766	
	(Except for		ASTM E1508	
	Those that			
	Release Gas			
	upon Exposure			
	to Vacuum			
Mechanical –	PQR and WPQ	Visual Inspection	API 1104	All Welding Processes
Welding	Testing	Charpy V-Notch	AWS D1.1, AWS	
Qualification		All Metal Weld Tensile	D1.5 ASTM A370	
Services FO		Properties		_
		Tensile Test, Bend Tests,	ASME IX,	
		Fillet Weld Break Tests,	API 1104,	
		Macro-Etching, Nick	AWS B2.1, D1.1,	
		Break Tests, Hardness	D1.2, D1.3, D1.4,	
		Profiles	D1.5, D1.6, D17.1	
Non-Destructive	Weld Flaw	Flaw Length / Width /	AWS D1.1	>5/16" to
Ultrasonic Testing	Detection	Depth / Indication	A-scan Longitudinal	8" Thickness
FO	/Material	Rating	Wave / A-scan	
	Thickness		ShearWave	
	Readings			
Non-Destructive	Weld and Base	Flaw Length / Width	ASTM E709	Surface and Slight
Magnetic Particle	Material Flaw		Wet / Dry /	Subsurface Flaws
Testing FO	Detection	1	Fluorescent / Yoke	
Non-Destructive			ASTM E165	Surface Flaws Only
Liquid Penetrant			Fluorescent / Visible	
Testing FO			Dye / Water	
			Washable / Solvent	
			Removed	

- 1. The presence of a superscript F means that the laboratory performs testing of the indicated parameter at its fixed location
- 2. The presence of a superscript FO means that the laboratory performs testing of the indicated parameter both at its fixed location and onsite at customer locations.